

MD300M

Handheld Pulse Oximeter

Pulse oximeter is a very important and common device to check patient pulse blood oxygen saturation (SpO₂) level and pulse rate. As a portable, compact, simple, reliable and durable physiological monitoring device, handheld pulse oximeter MD300M can greatly enhance patient care. It is widely applied in clinic, hospital, social medical organizations, and first aid and so on.



TECHNICAL SPECIFICATIONS

Patient Range

Adult and Pediatrics

SpO₂

Measurement range	70% - 100%
Resolution	1%
Measurement Accuracy	70% - 100%: ±3 Digit 0% - 69%: no definition

Pulse Rate

Measurement range	30 - 235bpm
Resolution	1bpm
Measurement accuracy	±2bpm or 2% (The larger)

Display

Type	2.8" color TFT
Parameters	SpO ₂ , PR, pulse bar, Plethysmogram
Brightness	Adjustable 1 - 7 level

Alarm

Alarm	SpO ₂ , PR, Probe off, Finger out Battery-low indicator
Modes	audio & visual alarm, information

Data management

Transmission method	USB Data cable
ID setup	1 - 127
Data record	72 hours

Mechanical

Dimension	125mm (L) * 60mm (W) * 30mm (H)
Weight	195g (excluding the batteries)

Power Supply

Type	3 AA alkaline batteries /Ni-MH batteries or adapter
Battery operation time	work for 16 hours continuously at most
AC adapter	Input Voltage: AC 100 - 240V Input Frequency: 47 - 63Hz Output Voltage: DC 5V±5% Output Current: 2A MAX

FEATURES

- ◇ High resolution 2.8" TFT screen displays SpO₂, PR, waveform and pulse bar
- ◇ Adjustable audible and visual alarms; battery-low indicator
- ◇ Adjustable backlight and voice
- ◇ 127 ID setup; 72-hour data storage and review
- ◇ MedView software for data analysis
- ◇ charger stand and AC/DC adapter are optional
- ◇ 3 AA alkaline batteries or Ni-MH batteries (rechargeable)
- ◇ Suitable for adult and pediatric
- ◇ Multi-language(Menu):English, French, German, Spanish, Italian, Japanese, Russian

Classification

According to the type of protection against electric shock:

Internal powered equipment and class II equipment

According to the degree of protection against ingress of water:
IPX1

Environment requirements

Operation Temperature	5°C - 40°C
Storage Temperature	-20°C - 55°C
Operation Humidity	≤80%, no condensation
Storage Humidity	≤93%, no condensation

Accessories

Standard accessories: Three AA alkaline batteries; One instruction manual; One adult finger probe, Model: M-50E; The key for screwing the screw; Software CD; USB Cable

Optional accessories: Binding sensor for pediatric, infant and neonatal (Pediatric 15-45 Kg, Infant 3-15 Kg), Model: M-50C; Fingertip sensor for pediatric, Model: M-50B; Soft sensor for pediatric (Pediatric 15-45 Kg, Infant 3-15 Kg), Model: M-50H; Soft sensor for adult, Model: M-50G; Charger Stand (with adapter and USB Cable)



AUTHORIZED AGENT

Beijing Choice Electronic Technology Co., Ltd

Add: 4th Floor, Jingyang Science and Technology Building, NO.15 Xijing Road,

Shijingshan District, Beijing 100041, P.R.China

Tel: +86 10 88204188 / 88203520

FAX: +86 10 88204632

Email: market@choicemmed.com

Website: www.choicemmed.com

CHOICEMMED
providing a better life

